

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

| | | |
|--|----------------|---|
| MANUFACTURER'S NAME Stamped Concrete | | EMERGENCY TELEPHONE NO. 619-433-7682 |
| ADDRESS (Number, Street, City, State, and ZIP Code) 303 Via EL Centro Oceanside, CA 92054 | | |
| CHEMICAL NAME AND SYNONYMS N/A (mixture) | | TRADE NAME AND SYNONYMS Dustone Color Seal |
| CHEMICAL FAMILY N/A | FORMULA N/A | |

SECTION II - HAZARDOUS INGREDIENTS

| PAINTS, PRESERVATIVES, & SOLVENTS | % | TLV (Units) | ALLOYS AND METALLIC COATINGS | % | TLV (Units) |
|---|-------|-------------|--|---|-------------|
| PIGMENTS | | | BASE METAL | | |
| CATALYST | | | ALLOYS | | |
| VEHICLE Polymer plus Proprietary additives | 57.5% | | METALLIC COATINGS | | |
| SOLVENT Water | 42.5% | | FILLER METAL PLUS COATING OR CORE FLUX | | |
| ADDITIVES | | | OTHERS | | |
| OTHERS | | | | | |
| HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES | | | | % | TLV (Units) |
| Product may contain traces of the following: | | | | | |
| Formaldehyde CAS No. 50-00-0 less than .0042% | | | | | |
| Acrylonitrile CAS No.107-13-1 less than .0001% | | | | | |

SECTION III - PHYSICAL DATA

| | | | |
|---|---------------|---------------------------------------|----------|
| BOILING POINT (°F.) | 212°F | SPECIFIC GRAVITY (H ₂ O=1) | 1 to 1.2 |
| VAPOR PRESSURE (mm Hg.) | same as water | PERCENT, VOLATILE BY VOLUME (%) | 64% |
| VAPOR DENSITY (AIR=1) | same as water | EVAPORATION RATE (_____ =1) | |
| SOLUBILITY IN WATER | Dilutable | | |
| APPEARANCE AND ODOR Viscous Liquid, mild odor, various colors | | | |

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

| | | | |
|--|------------------|-----|-----|
| FLASH POINT (Method used) N/A (Aqueous Systems) | FLAMMABLE LIMITS | Let | Uel |
| EXTINGUISHING MEDIA Exclude air, CO ₂ , Dry Chemical | | | |
| SPECIAL FIRE FIGHTING PROCEDURES Product may burn after water evaporates | | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS Product will not burn as supplied but may spatter if temp exceeds boiling point. Dried solids can burn after water evaporates | | | |

COLOR MAX

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

OSHA Permissible exposure not established

EFFECTS OF OVEREXPOSURE

May be irritating to eyes and skin. Vapors may also irritate nose and throat

EMERGENCY AND FIRST AID PROCEDURES

Eyes and skin: Flush eyes with large amounts of water, wash skin with soap and water.

If swallowed: Product is of very low acute Toxicity. There is no specific *antidote*

Treatment should be directed at control of symptoms and clinical condition

SECTION VI - REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

NONE

STABLE

X

INCOMPATIBILITY (Materials to avoid)

NONE

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

NONE

WILL NOT OCCUR

X

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Contain Spill: Return material to container

WASTE DISPOSAL METHOD

Dispose of in accordance with state and federal regulations. Do not incinerate closed containers

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

None required in well ventilate areas

VENTILATION

LOCAL EXHAUST

X

SPECIAL

MECHANICAL (General)

OTHER

PROTECTIVE GLOVES

Recommended

EYE PROTECTION

Use safety eyewear to protect against

OTHER PROTECTIVE EQUIPMENT

rubber boots and apron

splashing

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

OTHER PRECAUTIONS

Do not take internally -Keep out of reach of children