

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Stamped Concrete		EMERGENCY TELEPHONE NO. 619-433-7682
ADDRESS (Number, Street, City, State, and ZIP Code) 303 Via EL Centro Oceanside, CA 92054		
CHEMICAL NAME AND SYNONYMS (n/A) mixture		TRADE NAME AND SYNONYMS Dustone Colored Release
CHEMICAL FAMILY N/A	FORMULA N/A	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)	
PIGMENTS		N/A	BASE METAL		N/A	
CATALYST		N/A	ALLOYS		N/A	
VEHICLE		N/A	METALLIC COATINGS		N/A	
SOLVENTS		N/A	FILLER METAL PLUS COATING OR CORE FLUX		N/A	
ADDITIVES		N/A	OTHERS		N/A	
OTHERS		N/A			N/A	
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					%	TLV (Units)
Limestone 98.5% ^{WW} cas. 1317-65-3						
Silica Quartz 0.1 -1% ^{WW} cas. 14808-60-7						
Product contains trace amounts of arsenic-1 ppm, cadmium-5 ppm, lead-2 ppm						

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	1.06
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT, VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	NONE		
APPEARANCE AND ODOR Dry powder, various colors, slight odor			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	Lel	Uel
		not flammable		
EXTINGUISHING MEDIA				
SPECIAL FIRE FIGHTING PROCEDURES				
N/A				
UNUSUAL FIRE AND EXPLOSION HAZARDS				
not tested				

RELEASE

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE

airborne material irritating to the mucosa of the respiratory system causing sneezing and coughing

EMERGENCY AND FIRST AID PROCEDURES

remove to fresh air & obtain medical advice if required

SECTION VI - REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

STABLE

X

none

INCOMPATIBILITY (Materials to avoid)

strong acid

HAZARDOUS DECOMPOSITION PRODUCTS

none

HAZARDOUS POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

concentrated dusty conditions

WILL NOT OCCUR

X

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

normal cleanup

WASTE DISPOSAL METHOD

normal waste disposal

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

dust mask recommended - NIOSH or OSHA approved

VENTILATION

LOCAL EXHAUST

recommended

SPECIAL

MECHANICAL (General)

if needed

OTHER

PROTECTIVE GLOVES

recommended

EYE PROTECTION

recommended

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep out of reach of children, Do not take internally

OTHER PRECAUTIONS